

# C800

Ultra-light x86 Thin Client supporting Microsoft RDP, Citrix, VMware View



## Feature


- Ultra-light and fanless design
- Designed with Intel Bay Trail-M platform Dual-Core CPU
- Support Microsoft RDP, Citrix, VMware View
- Optional WLAN module
- Support Kensington lock and VESA mount

## Specification


Processor	CPU	Intel Celeron N2807 Dual-Core 1.58GHz up to 2.16GHz (burst frequency)		
Memory	RAM	x1 SO-DIMM socket for DDR3L 1333MHz RAM up to 8GB		
Display	Resolution	up to 1920 x1200		
	Graphic Engine	Intel Gen7		
Audio	Speaker	x1 (Built-in 1W internal speaker)		
Storage	x1 onboard eMMC (4GB/ 16GB)			
	x1 mSATA connector			
I/O Physical	DVI-I	x1		
	DVI-D	x1		
	USB 3.0	x1 (rear x1)		
	USB 2.0	x3 (front x3)		
	Mic-in	x1		
	Line-out	x1		
Networking	LAN	x1 (RJ-45, 10/100/1000 Base-T)		
	WLAN	(Optional, mini-PCIe interface*)		
Environment	Temperature	Operation	32° to 104° F (0° to 40° C)	
		Storage	-4° to 140° F (-20° to 60° C)	
	Relative Humidity	20% to 80% non-condensing		
Power	Power Supply	24W, DC 12V/2A external power adapter		
Mounting	Foot Stand	Vertical		
	VESA Bracket	(optional)		
Security	Kensington Lock	Yes		
OS support	Win7(WES7), Win8/8.1(WES8), Linux			
Physical Characteristics	Chassis Housing		Plastic and metal	
	Dimension	Terminal	35 (W) x 155 (H) x 120(D) mm	
		Packing : Single Box	83 (W) x 232 (H) x 205 (D) mm, Weight: 1.3 KG	
		Packing : Carton	662 (W) x 265 (H) x 355 (D) mm, 12 in 1	
Regulatory Compliance		CE/ FCC		

## Drawing

Front View



Rear View



Front View

1. Power button
2. USB 2.0
3. Line-out
4. MIC-in
5. Cradle

Rear View

6. Reserved hole for external antenna
7. USB 3.0
8. RJ-45
9. DVI-I
10. DVI-D
11. DC jack
12. Kensington Lock

Specifications subject to change without notice.

\* Note: For mini PCIe interface of C800, USB signal is not supported

